

ISO 9001 CERTIFIED

ISSUED DATE: 01/06/2007

Novamid ® B27 are Polyamide 6 pellets produced by the CPL reaction in polymerisation.

Product properties	Specification	Standard method
Relative viscosity	2,70 ± 0,1	ISO 1628 1% in SO4H2 - 96% at 25°C
Monomer % max.	0,6	ISO 599
Moisture content % max.	0,1	NAPPA - 032

Product description	Unit	Value	Testing method
Melting point	°C	223	ISO 3146
Density	g/cm ³	1,12	ISO 1183
Apparent density	g/cm ³	0,67	NAPPA - 059
Chip size (length-diameter)	mm	1,5 2,5	NAPPA - 045
Colour		Bright	

Packaging	Big bag / 1000 kgs Octabin / Silo truck
-----------	---

All the information submitted is based on our knowledge and experience. The shown values have been established by using standardised tests performed at our plant. Figures should be regarded as guidance and not as a minimum values. The affectation of the process and applications by different factors or conditions cannot be guaranteed, therefore, users are recommended to perform the test in order to determine the suitability of the product for one particular use.

Central offices

Independencia, 21. 3^a
50001 Zaragoza. Spain
T +34 976 216 129
F +34 976 238 703
www.novamid.com

Plant

Polígono de Malpica, Ctra de Barcelona, Km 329.2
50016 Zaragoza. Spain
T +34 976 465 579
F +34 976 574 108